

MEBULBS.COM

Product Code =	B2T618
Description =	L18.5T8/4FT/VLX/BYP-SE-DE/SG/9Y
Type =	LED Bypass Type B Internal Driver (Fluorescent Retrofit)
Operating Design =	SE-DE (works on both SE single-end non-shunted and DE double-end shunted bypass wiring scenarios)
Color Temperature =	VITALUX™-5500°K
Color Rendering Index (CRI) =	82
Operating Temperature =	-4°F to +110°F
Photopic Lumens =	2,600
Projected Seeable Lumens™ =	4,810
Nominal Length =	48"
Tube Diameter /Material =	1" (T8) Glass
Safety-Coated =	Yes
Location =	Damp-rated (IP20 rated), can be used in enclosed fixtures
Nominal Wattage =	18.5w
Input Voltage =	175mA
Power Factor/THD =	0.9PF/8.5%THD
Design Hours =	50,000+ hours
Light Distribution =	240° wide angle
Input Voltage =	120-277VAC line voltage (Not for use on fluorescent ballasts)
Base =	Medium Bi-Pin (G13)
End Pins =	Nickel-Plated Brass
End Cap =	Plastic-White Color
LED Chips =	Hi-Efficiency
Mercury/UV =	None/None
UL Listed =	Yes
Dimmable =	No
Warranty =	9-years



*Specifications subject to change without notice.

081121

Premium Quality Lighting