



CBU134 XTREME DUTY • 7YR **LED HYBRID LINEAR T8/U6 DUAL MODE INTERNAL DRIVER** (UL TYPE A AND TYPE B)

FEATURES

The LED T8 Hybrid U6 lamp provides exceptional lighting with reduced energy and maintenance costs. The hybrid tube works with or without a ballast, making it a top-ofthe-line replacement for standard fluorescent lamps.

DIRECT INSTALL OR DIRECT WIRE - SINGLE / DOUBLE ENDED

Use with an instant start ballast as a direct replacement lamp or simple rewiring allows lamp to run directly off the main.

- Thermal fuse for added safety
- Exceptional efficacy
- Tubes will work with shunted and non-shunted sockets (See Additional Information on Page 2)

ELECTRICAL	LAMP	SYSTEM POWER	
Wattage	13W	16W	
Voltage	120-277V		
Power Factor	0.9		
Total Harmonic Distortion (THD)	20		
LIGHTING PERFORMANCE			
Lumens	1900		
Lumens Per Watt (LPW)	125		
Color Temperature (CCT)	4000K		
Color Rendering (CRI)	83		
R9 (Red Value)	1		
R13 (Skin Tones)			
Beam Angle	160°		
Light Distribution	Тур	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	2 Lamp	B1 - U2 - G	
ENVIRONMENT			
Operating Temperature	-4° ~ 113°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP20		
Suitable Fixture Type	Enclosed		
Suitable for Emergency Fixtures/Ballasts	No		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	7		
COMPONENTS			
LED Light Source	Samsung SPMWH1228		
CONSTRUCTION			
Housing	PC / Plastic End Caps		
Lens	Frosted		
Base / Power Supply	G13 - Medium Bi Pin		
QUALIFICATIONS			
	90440		




Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

CBU134 XTREME DUTY • 7YR LED HYBRID LINEAR T8/U6



DIMENSIONS (Inches)	
Length (MOL)	22.3"
Width/Diameter (MOD)	7.1"
Net Weight (Lbs)	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	12	10811768022268	24.4" x 15.2" x 8.3"	10.8
Individual Box	1	811768022261	23" x 7.2" x 1.1"	0.9
Country of Origin	China			
HS Tariff	8539.50.0010			

ORDERING

ITEM#	DESCRIPTION	CASE
CBU134	LED 13WT8/U6/40K/TYPE A & B	12

Manufactured by P.Q.L., Inc. - Manufacturer Model # 90440

ADDITIONAL INFORMATION:

• In direct wire application; shunted sockets use double ended wiring only and non-shunted can use either single or double ended wiring. Please refer to install instructions for further details.