



XTREME DUTY

CDX348A

FEATURES

Spec-Select™ LED Designer Strip offer the flexibility of 9 fixtures in 1, delivering energy-efficient, adjustable lighting for a perfect fit in any environment.

- Selectable wattage: Three adjustable output settings for onsite flexibility.
- Selectable CCT: Choose from three color temperatures.
- Sensor Ready: Integrated Sensor Option (ISO); compatible plug-in motion and daylight sensor and elbow sold separately.
- Surface or chain mounting; single or continuous row.

APPLICATION

Perfect for offices, warehouses, parking garages, schools, corridors, and other commercial or industrial applications.

PRODUCT INFORMATION

ELECTRICAL		
Wattages (Selectable)	18W / 25W / 30W	
Voltage	120-277V	
Current	30W @ 120V = 0.25A	
Power Factor	0.9	
THD	12.7	

OPTICAL		
Lumens	2376 / 3300 / 3960	
Efficiency (LPW)	132	
CCT (Selectable)	3500K / 4100K / 5000K	
CRI	82	
Beam Angle	130°	
Dimming	From optional sensor, or customer 0-10V controls	

ENVIRONMENT	
Operating Temperature	-4°F ~ 122°F
Suitable Location	Damp

CONSTRUCTION		
LED Chip	Bridgelux	
Driver	SIF30-I0650-SS	
Sensor Socket	12VDC Aux.	
Housing	Aluminum	
Lens	Frosted	
Base / Power Supply	Hard Wired	
Finish	White	

LIFESPAN (Complete terms can be found on our website.)	
Life Hours (Avg.)	50,000
Warranty (Years)	7

LISTINGS	
Model Number	55762




CDX348A



100

DIMENSIONS



ORDERING

CODE	DESCRIPTION	CASE
CDX348A	LED 4FT SPEC-SELECT™ NARROW DESIGNER STRIP/18-25-30W/35-50K/DIMM/ISO/120-277V	9
ACCESSORIES		
LVSEN1	BI-LEVEL PIR MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT (REQUIRES 12-24VDC AUX & ELBOW #LVELBO)	100
LVSEN2	BI-LEVEL MICROWAVE MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT	100

EXTERNAL SWIVEL QUICK CONNECT ADJUSTABLE ELBOW FOR LVSEN1/LVSEN2 (For best sensor performance.)

PACKAGING

LVELBO

MASTER CASE		
Quantity	9	
Size (LxWxH)	49.6." x 11.7" x 8.3"	
Gross Weight (Lbs)	37.9	
UPC	10811768028840	
INDIVIDUAL BOX		
Dimensions (LxWxH)	48.6" x 2.2" x 2.7"	
Gross Weight (Lbs)	6.3	
UPC Item	811768028843	

(REQUIRES 12-24VDC AUX & ELBOW #LVELBO)

Tariff: 9405.11.6020

NOTES

- Default settings; 18W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver, selection should be made prior to installation. See installs for full details.