



XTREME DUTY

CDX596A

FEATURES

Spec-Select™ LED Designer Strip offer the flexibility of 9 fixtures in 1, delivering energy-efficient, adjustable lighting for a perfect fit in any environment.

- Selectable wattage: Three adjustable output settings for onsite flexibility.
- Selectable CCT: Choose from three color temperatures.
- Sensor Ready: Integrated Sensor Option (ISO); compatible plug-in motion and daylight sensor and elbow sold separately.
- Surface or chain mounting; single or continuous row.

APPLICATION

Perfect for offices, warehouses, parking garages, schools, corridors, and other commercial or industrial applications.

PRODUCT INFORMATION

ELECTRICAL		
Wattages (Selectable)	38W / 46W / 54W	
Voltage	120-277V	
Current	54W @ 120V = 0.45A	
Power Factor	0.9	
THD	10.4	

OPTICAL		
Lumens	5016 / 6072 / 7128	
Efficiency (LPW)	132	
CCT (Selectable)	3500K / 4100K / 5000K	
CRI	82	
Beam Angle	130°	
Dimming	From optional sensor, or customer 0-10V controls	

ENVIRONMENT	
Operating Temperature	-4°F ~ 122°F
Suitable Location	Damp

CONSTRUCTION		
LED Chip	Bridgelux	
Driver	SIF50-l1200-SS	
Sensor Socket	12VDC Aux.	
Housing	Aluminum	
Lens	Frosted	
Base / Power Supply	Hard Wired	
Finish	White	

LIFESPAN (Complete terms can be found on our website.)		
Life Ho	urs (Avg.)	50,000
Warran	ty (Years)	7


LISTINGS	
Model Number	55764



CDX596A



DIMENSIONS



ORDERING

CODE	DESCRIPTION	CASE
CDX596A	LED 8FT SPEC-SELECT™ NARROW DESIGNER STRIP/38-46-54W/35-50K/DIMM/ISO/120-277V	4
ACCESSORIES		
BLI EVEL PIR MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT		

LVSEN1	BI-LEVEL PIR MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT (REQUIRES 12-24VDC AUX & ELBOW #LVELBO)	100
LVSEN2	BI-LEVEL MICROWAVE MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT (REQUIRES 12-24VDC AUX & ELBOW #LVELBO)	100
LVELBO	EXTERNAL SWIVEL QUICK CONNECT ADJUSTABLE ELBOW FOR LVSEN1/LVSEN2 (For best sensor performance.)	100

PACKAGING

MASTER CASE		
Quantity	4	
Size (LxWxH)	97.4." x 4.6" x 4.3"	
Gross Weight (Lbs)	13.4	
UPC	10899645001049	
INDIVIDUAL BOX		
Dimensions (LxWxH)	95.5" x 2.2" x 2.7"	
Gross Weight (Lbs)	3.4	
UPC Item	899645001042	

Tariff: 9405.11.6020

NOTES

- Default settings; 38W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver, selection should be made prior to installation. See installs for full details.