



CF3225 XTREME DUTY • 7YR LED 2X2 PREMIUM PANEL

2X2 LUMINARIES FOR AMBIENT LIGHTING OF
INTERIOR COMMERCIAL SPACES

FEATURES

- High Efficiency, Energy Saving
- Highest lumens per watt light output.
- Low glare, bright edge-to-edge lighting.
- For covered ceilings only
- Earthquake proof hooks included

APPLICATION

Ideal for offices, conference rooms, hospitals, lobbies, hotels, classrooms, workshops, cafeterias and other common areas.

ELECTRICAL

Wattage	36W
Voltage	100-277V
Current	850mA
Power Factor	0.9
Total Harmonic Distortion (THD)	11.2

LIGHTING PERFORMANCE

Lumens	4700
Lumens Per Watt (Lm/W)	130
Color Temperature (CCT)	5000K
Color Rendering (CRI)	83
R9 (Red Value)	N/A
R13 (Skin Tones)	N/A
Beam Angle	120°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B2 - U1 - G1
Dimmable Lighting Control	<i>Dimmable</i> 1-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4 ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	7

COMPONENTS

LED Light Source	Everlight 67-21S
Driver	554156

CONSTRUCTION

Housing	Aluminum
Lens	--
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS

Manufacturer Model #	55415
----------------------	-------



Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.



CF3225 XTREME DUTY • 7YR LED 2X2 PREMIUM PANEL



DIMENSIONS (Inches)

Length	23.7"
Width/Diameter	23.7"
Height	1.7"
Weight (Lbs)	6.6

Line drawings may not be to scale and are for general reference only.



TOP VIEW

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	2	10811768021735	25.6" x 25.6" x 4.5"	17.3
Individual Box	1	811768021738	--	8.7
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
CF3225	LED 2X2 PANEL - 36W/50K/120-277V/DIMMABLE/V6	2

Manufactured by P.Q.L., Inc. - Manufacturer Model # 55415

ACCESSORIES

LF3505	EMERGENCY PACK FOR LED PANEL 15W/90 MIN	6
LF3506	EMERGENCY PACK FOR LED PANEL 25W/90 MIN	6

PERFORMANCE DATA

PACKAGING