



CFLX20 XTREME DUTY • 7YR LED SPEC-SELECT™ FLOOD LIGHT

FEATURES

- Adjustable wattage and color temperature.
- Integrated photocell with On/Off switch.
- Corrosion resistant die cast housing, with a powder paint coat finish.
- · Compact design.
- Fixture angle can be easily adjusted.

APPLICATION

Ideal for wall washing, landscaping lighting, outdoor advertising and parking lots.

ELECTRICAL

Wattage	100W / 150W / 200W		
Voltage	120-277V		
Power Factor	0.9		
Total Harmonic Distortion (THD)	20		
LIGHTING PERFORMANCE			
Lumens	15000 / 22500 / 30000		
Lumens Per Watt (LPW)	150		
Color Temperature (CCT)	3000K / 4000K / 5000K		
Color Rendering (CRI)	80		
R9 (Red Value)	5		
R13 (Skin Tones)			
Beam Angle	7H x 7V		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B4 - Ux - G2		
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%		
ENVIRONMENT			
Operating Temperature	-4° ~ 104°F		
Suitable Location	WET		
Ingress Protection Rating	IP65		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	7		
COMPONENTS			
LED Light Source			
Driver	Premium Electronics with 6kV/4kV Surge Protection		
CONSTRUCTION			
Housing	Die Cast Aluminum		
Lens	PC		
Base / Power Supply	Hard Wired		
Finish	Bronze		
QUALIFICATIONS			



Manufacturer Model #


Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

84363

CFLX20 XTREME DUTY • 7YR LED SPEC-SELECT™ FLOOD LIGHT



DIMENSIONS (Inches)		
Length	13.4"	
Width	3.4"	
Height	10"	
Weight (Lbs)		



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768021752	16.3" x 5.2" x 11.9"	
Country of Origin	China			
HS Tariff	9405.11.6020			

ORDERING

ITEM#	DESCRIPTION	CASE		
CFLX20	LED SPEC-SELECT™ FL00D/100-150-200W/30-40-50K/DIMM/120-277V/BRZ/PC	1		
Manufactured by P.Q.L., Inc Manufacturer Model # 84363				
ACCESSOR	IES			
LFLXTN	SLIP FITTER MOUNT ONLY FOR LED FLOOD LIGHT/BRZ	6		
LFLXUB	U-MOUNT ONLY FOR LED FLOOD LIGHT/BRZ	20		