

20250 / 23250 / 27750





CH5112 XTREME DUTY • 8YR LED 2' SPEC-SELECT™ LINEAR HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

FEATURES

- Selectable wattage and color temperature
- High lumen output bright and high lumen per watt.
- Integrated LED maintenance free.
- · Replaces HID and fluorescent fixtures.
- · Wide beam angle uniform light distribution.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.
- · Pre-installed sensor socket.

MOUNTING

Designed for suspended or pendent mounting. (*V-hooks & 41.3" chains included*)

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Lumens

Wattage	135W / 155W / 185W
Voltage	120-277V
Current	185W = 1.5A @ 120V
Power Factor	0.9
Total Harmonic Distortion (THD)	8.4

LIGHTING PERFORMANCE

Editiono	20200 / 20200 / 21100	
Lumens Per Watt (LPW)	150	
Color Temperature (CCT)	4000K / 5000K	
Color Rendering (CRI)	81	
R9 (Red Value)	-6	
Beam Angle	120°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B4 - U3 - G2	
Dimmable Lighting Control	From optional 12VDC sensor, or customer 0-10V controls.	

ENVIRONMENT

Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	8

COMPONENTS

LED Light Source Bridgelux	
Driver	SIL80-I2000 & SIL80-I2000 DS
Sensor Socket	12VDC AUX.

CONSTRUCTION

Housing	24 Gauge C.R.S.
Lens	Acrylic (PMMA)
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS

Manufacturer Model # 55715




Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

CH5112 XTREME DUTY • 8YR LED 2' SPEC-SELECT™ LINEAR HIGH BAY



DIMENSIONS (Inches)	
Length	24.8"
Width	18.9"
Height	2.2"
Net Weight (Lbs)	11.2
Chain Length	41.3" (2 ea.)



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	854432004552	25.6" x 19.2" x 2.4"	
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
CH5112	LED 2FT SPEC-SELECT™ LINEAR HL HIGH BAY/135-155-185W/40-50K/DIMM/ISO/120-277V	1

Manufactured by P.Q.L., Inc. - Manufacturer Model # 55715

ADDITIONAL INFORMATION:

Default settings: 135W, 5000K

Note: When using an Emergency Pack with the fixture, cable mounting is recommended to control the balance of the fixture.