



**CRO244 XTREME DUTY • 7YR
LED 2X4 TROFFER RETROFIT/
CENTER BASKET**
INTEGRATED RETROFIT KITS FOR 2X4 LUMINAIRES

FEATURES

- Provides smooth uniform light.
- Low-profile which meets limitless range of applications.
- Use 30% less energy than a linear fluorescent fixtures.
- All steel surfaces are painted after fabrication with high gloss baked white matte powder paint.
- No need to remove existing fixture for retrofit application.

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Wattage	45W
Voltage	120-277V
Current	0.37A
Power Factor	0.9
Total Harmonic Distortion (THD)	10

LIGHTING PERFORMANCE

Lumens	5040
Lumens Per Watt (LPW)	112
Color Temperature (CCT)	4000K
Color Rendering (CRI)	82
R9 (Red Value)	--
R13 (Skin Tones)	--
Beam Angle	100°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	--
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	7

COMPONENTS

LED Light Source	--
Driver	--

CONSTRUCTION

Housing	24 Gauge Steel
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS

Model Number	55097
--------------	-------



Manufactured by P.Q.L., Inc. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.


CRO244 XTREME DUTY • 7YR LED 2X4 TROFFER RETROFIT/CENTER BASKET



ITEM INFORMATION

DIMENSIONS (Inches)

Length	47.8"
Width	23.9"
Height	3.1"
Net Weight (Lbs)	14



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	899645001783	48.5" x 24.4" x 3.3"	17.6
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
CRO244	LED 2X4 CENTER BASKET TROFFER RETROFIT/45W/40K/DIMM/120-277V	1

Manufactured by P.Q.L., Inc. - Manufacturer Model # 55097

ACCESSORIES

LF3502	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN/SPLIT TYPE/L - T20C (For use with drivers that are 100W or less.)	10
--------	--	----