





# CSB322 XTREME DUTY • 7YR LED 2X2 SPECTRA<sup>™</sup> BACK-LIT PANEL

2X2 LUMINARIES FOR AMBIENT LIGHTING OF INTERIOR COMMERCIAL SPACES

### **FEATURES**

Spectra<sup>™</sup> Panels offer flexible and custom lighting solutions based on an individuals needs and activities. When paired with a Spectra<sup>™</sup> remote or wireless wall dimmer<sup>\*</sup>, our Spectra<sup>™</sup> Panels are adjustable for both Brightness and Color for the perfect balance of light for any situation.

- Energy efficient
- No flickering
- RF 2.4GHz Wireless

\*Handheld remote and wireless wall dimmer, sold separately

## **APPLICATION**

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, lobbies and other residential and commercial applications.

Default setting CCT 4000K at full brightness as shipped.

### ELECTRICAL

Wattage	35W	
Voltage	120-277V	
Current	140-400mA	
Power Factor	0.9	
Total Harmonic Distortion (THD)	15%	
LIGHTING PERFORMANCE		
Lumens	4550	
Lumens Per Watt (Lm/W)	130	
Color Temperature (CCT)	5000K-3000K	
Color Rendering (CRI)	80	
Beam Angle	120°	
Dimmable Lighting Control	0-10V, to 10%	
ENVIRONMENT		
Operating Temperature	-4° ~ 122°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP40	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	7	
COMPONENTS		
LED Light Source		
Driver	JPB40LRF054R22	
CONSTRUCTION		
Housing	Aluminum	
Lens	UV-Stabilized Polycarbonate	
Base / Power Supply	Hard Wired	
Finish	White	

## QUALIFICATIONS

Model Number

SPC12235ACUW



Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

# CSB322 XTREME DUTY • 7YR LED 2X2 SPECTRA<sup>™</sup> BACK-LIT PANEL




### **DIMENSIONS** (Inches)

Length	23.7"
Width	23.7"
Height	1.4"
Net Weight (Lbs)	

### PACKAGING

Master Case	2
Dimensions	24.6" x 24.8" x 3.1"
Country of Origin	China
HS Tariff	



1

## ORDERING

LBSM22

ITEM#	DESCRIPTION	CASE
CSB322	2 X 2 PANEL-BACK-LIT SPECTRA 35W/120-277V/0-10 DIM	1
Manufactured b	y P.Q.L., Inc Manufacturer Model # SPC1-22-35-AC-U-W	
ACCESSORI	ES	
LSBREM	HANDHELD REMOTE for BACK-LIT SPECTRA - UP TO 4 ZONES (batteries not included, requires 2-AAA)	1
LSBWWD	WALL REMOTE for BACK-LIT SPECTRA - 1 ZONE (batteries not included, requires 2-AA)	1



SURFACE MOUNT KIT FOR 2X2 BACK-LIT FLAT PANEL

HANDHELD REMOTE LSBREM



WALL REMOTE LSBWWD



SURFACE MOUNT KIT LBSM22

### **ADDITIONAL INFORMATION**

- New Spectra panels are not compatible with previous generations of Spectra remote controls; they only operate with the LSBREM or LSBWWD controls.
- A common 0-10V dimmer can be used with this panel. (Color temperature is only adjustable with the handheld remote or wireless wall dimmer.)
- Each controller (handheld remote or wireless wall dimmer) can control multiple panels as long as the distance between the panel and controller is within 98 feet, and signal is not obstructed between fixture and controller (wall, column, etc.).
- Panel(s) can be paired to (1) handheld remote control and (1) wireless wall dimmer. They cannot be paired to multiple handheld remote controls or multiple wireless wall dimmers.
- If using the handheld remote (LSBREM) or wireless wall dimmer (LSBWWD) with the Spectra panel, they cannot be the only on-off switch; it must be used together with
  a hard-wired on/off switch. The fixture needs to be turned off for the night with a standard hard-wired wall switch (or at the breaker panel).