



CVX225 XTREME DUTY • 7YR LED 2' SPEC-SELECT™ VAPOR TIGHT DIRECT LINEAR AMBIENT LUMINARIES

FEATURES

Spec-Select™ Vapor Tights are like 9 fixtures in 1, featuring adjustable wattage and color temperature for the perfect balance of light in any application.

- Adjustable Wattage (3 settings)
- Adjustable Color (3 settings)
- 5VA housing, meets highest UL94 Standards.
- Liquid silicone perimeter gasket formed to housing provides a seamless seal and protects from dust and humidity.
- Stainless steel clips.
- Sufficient knockouts are available.

APPLICATION

Ideal for commercial and industrial environments; tunnels, stairwells, parking garages, cold storage, and airports. *Not designed for use in car washes, truck wash bays, or where exposed to harsh chemicals.*

ELECTRICAL

Wattage	15W / 20W / 25W
Voltage	120-277V
Current	25W @ 120V = 0.20A
Power Factor	0.9
Total Harmonic Distortion (THD)	5.5

LIGHTING PERFORMANCE

Lumens	1995 / 2660 / 3325
Lumens Per Watt (LPW)	133
Color Temperature (CCT)	3500K / 4100K / 5000K
Color Rendering (CRI)	81
R9 (Red Value)	4
Beam Angle	120°
Dimmable Lighting Control	From optional 12VDC sensor, or customer 0-10V controls.

ENVIRONMENT

Operating Temperature (Suspended at least 18" from ceiling)	-40° ~ 113°F
Operating Temperature (Surface Mount)	-40° ~ 104°F
Suitable Location	WET
Ingress Protection Rating	IP65

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	7

COMPONENTS

LED Light Source	Bridgelux
Driver	SIL50-I550-SS

CONSTRUCTION

Housing	Polycarbonate
Lens	Frosted
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS

Model Number	55682
--------------	-------



Manufactured by PQL, Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


CVX225 XTREME DUTY • 7YR
LED 2' SPEC-SELECT™ VAPOR TIGHT



ITEM INFORMATION

DIMENSIONS (Inches)

Length	23.6"
Width	3.5"
Height	3.1"
Net Weight (Lbs)	--



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	4	10811768024057	25.8" x 8.5" x 7.1"	11.6
Individual Box	1	811768024050	25" x 3.9" x 3.2"	2.9
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
CVX25	LED 2FT SPEC-SELECT™ VAPOR TIGHT/15-20-25W/35-50K/DIMM/ISO/120-277V	4

Manufactured by P.Q.L., Inc. - Manufacturer Model # 55682

ACCESSORIES

LVSEN1	BI-LEVEL PIR MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT (REQUIRES 12-24VDC AUX & ELBOW #LVELBO)	100
LVSEN2	BI-LEVEL MICROWAVE MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT (REQUIRES 12-24VDC AUX & ELBOW #LVELBO)	100
LVELBO	EXTERNAL SWIVEL QUICK CONNECT ELBOW (For best sensor performance.)	100