





# LBDL24 COMMERCIAL DUTY • 5YR LED SPEC-SELECT™ BOLLARD HEAD

**OUTDOOR DECORATIVE LIGHTING** 

### **FEATURES**

- Adjustable wattage (3 settings)
- Adjustable light color (3 settings)
- Contemporary design
- · Corrosion resistant exterior
- Easy installation, switchable bollard heads
- Integrated photocell with On/Off switch

#### **APPLICATION**

Versatile decorative lighting for residential, industrial and commercial applications. Commonly used to illuminate walkways, entrances, or driveways for added safety and security.

\* Requires bollard tube/base (#BDBASE)

#### **ELECTRICAL**

Wattage	14W / 19W / 24W		
Voltage	120-277V		
Power Factor	0.9		
Total Harmonic Distortion (THD)			
LIGHTING PERFORMANCE			
Lumens	1750 / 2300 / 3000		
Lumens Per Watt (LPW)	125		
Color Temperature (CCT)	3000K / 4000K / 5000K		
Color Rendering (CRI)	70		
Beam Angle	360°		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G2		
Dimmable Lighting Control	<b>("Dimmable</b> 0-10V, Range 10% - 100%		
ENVIRONMENT			
Operating Temperature	-40° ~ 122°F		
Suitable Location	WET		
Ingress Protection Rating	IP65		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	Bridgelux		
Driver	IS030062035-32F		
CONSTRUCTION			
Housing	Die cast Aluminum		
Lens	Clear		
Base / Power Supply	Hard Wired		
Finish	Bronze		



QUALIFICATIONS

Model Number


Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

BLRD-DL-14/19/24W-3CCT-PC

# LBDL24 COMMERCIAL DUTY • 5YR LED SPEC-SELECT™ BOLLARD HEAD



DIMENSIONS (Inches)	
Width/Diameter	6.3"
Height (With round base)	43.7"
Net Weight (Lbs)	



* Base sold
separately.

PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	4	10811768021766	16.9" x 16.9" x 15"	21.9
Individual Box	1	811768021769	8.1" x 8.1" x 14.3"	5.5
Country of Origin	China			
HS Tariff	9405.11.6020			

#### **ORDERING**

ITEM#	DESCRIPTION	CASE
LBDL24	LED SPEC-SELECT™ BOLLARD ROUND/DOME TOP/LOUVER/14-19-24W/30-40-50K/DIMM/120-277V/BRZ/PC	4
Manufactured b	r P.Q.L., Inc Manufacturer Model # BLRD-DL-14/19/24W-3CCT-PC	
ACCESSORIES (Base required to complete installation.)		
BDBASE	LED SPEC-SELECT™ BOLLARD ROUND BASE/BRZ	1

## **ADDITIONAL INFORMATION:**

• The wattage, color temperature and photocell option may be selected by dip switches location on the bottom of the bollard head. Refer to install instructions for additional information.