



LD8384 LT. COMMERCIAL • 5YR LED 96" DESIGNER STRIP

DIRECT LINEAR AMBIENT LUMINARIES

FEATURES

- Diffusing lens for bright, uniform light.
- Low-profile with a limitless range of applications.
- Use 30% less energy than a linear fluorescent fixture.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.

MOUNTING

- Designed for surface or suspended chain mounting; individually or in a continuous row.

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

EL	C	U.	т	D	r	ΛI	ı
	c	b	Ш	n	U	M	L

ELECTRICAL			
Wattage	38W		
Voltage	120-277V		
Current	0.311A		
Power Factor	0.9		
Total Harmonic Distortion (THD)	10		
LIGHTING PERFORMANCE			
Lumens	4940		
Lumens Per Watt (Lm/W)	130		
Color Temperature (CCT)	4000K		
Color Rendering (CRI)	80		
R9 (Red Value)	15		
R13 (Skin Tones)	84		
Beam Angle	130°		
Light Distribution	Type II, Very Short		
Dimmable Lighting Control	("Dimmable 0-10V, Range 10% - 100%		
ENVIRONMENT			
Operating Temperature	-4° ~ 122°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP40		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	Seoul 3528		
Driver	ESPEN VPL50-115-MVHDA		
CONSTRUCTION			
Housing	24 Gauge Steel		
Base / Power Supply	Hard Wired		
Finish	White		
QUALIFICATIONS			
Manufacturer Model #	55241		



Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly.


LD8384 LT. COMMERCIAL • 5YR LED 96" DESIGNER STRIP



DIM	EN	SIO	INS	(Inches))

Length	96"
Width/Diameter	3.4"
Height	3.6"
Weight (Lbs)	

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	6	10811768027263		
Individual Box	1	811768027266		
Country of Origin	China			
HS Tariff	9405.40.6000			

ORDERING

ITEM#	DESCRIPTION	CASE
LD8384	96" DESIGNER 38W 4000K 120-277V DIMMABLE	6

Manufactured by P.Q.L., Inc. - Manufacturer Model # 55241