



# LF0184 LT. COMMERCIAL • 5YR **LED FLOOD LIGHT**

**ARCHITECTURAL FLOOD AND SPOT LUMINAIRES** 

## **FEATURES**

- High pressure die casting housing, anti-static powder
- High thermal conductive material and high efficiency cooling system.
- Fixture angle can be easily adjusted.
- Slip fitter mounting fits a 2 3/8" O.D. Tenon.

## **APPLICATION**

Ideal for wall washing, landscaping lighting, outdoor advertising and parking lots.

CI	ECTDICAL	

ELECTRICAL		
Wattage	80W	
Voltage	120-277V	
Current	0.671A	
Power Factor	0.9	
Total Harmonic Distortion (THD)	6.6	
LIGHTING PERFORMANCE		
Lumens	9300	
Lumens Per Watt (Lm/W)	116	
Color Temperature (CCT)	4000K	
Color Rendering (CRI)	70	
R9 (Red Value)	-18	
R13 (Skin Tones)	N/A	
Beam Angle	80°	
Light Distribution	Type IV, Very Short	
Dimmable Lighting Control	OUT DIMENSILS	
ENVIRONMENT		
Operating Temperature	-13° ~ 104°F	
Suitable Location	WET	
Ingress Protection Rating	IP65	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Seoul SW85F1C	
Driver	Arcata SLP80	
CONSTRUCTION		
Housing	Aluminum	
Lens	Tempered Glass	
Base / Power Supply	Hard Wired	
Finish	Black	
QUALIFICATIONS		
Manufacturer Model #	83325	
RoHS compliant		



Manufactured by P.Q.L., Inc. - Published lumens on LED products are approximate and may vary slightly.


# LF0184 LT. COMMERCIAL • 5YR LED FLOOD LIGHT



### **DIMENSIONS** (Inches)

Length	13.9"
Width	12.6"
Diameter	9.5"
Weight (Lbs)	28.3

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	<b>GROSS WEIGHT</b> (Lbs)
Master Carton	1	811768028966	15.4" x 13.4" x 11.4"	30
Country of Origin	China			
HS Tariff	9405.40.6000			

### **ORDERING**

ITEM#	DESCRIPTION	CASE
LF0184	LED 80W LARGE FLOOD LIGHT/40K/120-277V/SLIP FITTER	1

Manufactured by P.Q.L., Inc. - Manufacturer Model # 83325