

### FEATURES



Our T5 LED tube can work with the most popular electronic ballasts that are capable of replacing your existing fluorescent T5 lamps without any additional wiring. It provides exceptional LED lighting with reduced energy and maintenance costs.

- **Plug & Go™ - Works with existing electronic ballast\***
- Direct replacement for F54T5/H0
- Exceptional efficacy
- No flickering


*\*\*Suitable for dimming and emergency ballasts.  
F54T5 ballasts are programmable.*

### SPECIFICATIONS

<b>Power Consumption</b>	<b>30W</b>
Input Voltage	120-277V
Power Factor	0.9
Lumens	3500
Luminous Efficiency	117 Lm/W
Color Temperature	5000K
CRI	82
Beam Angle	180°
Dimension (Inches)	45.5"(L) x 0.62"(DIA)
<b>LIFESPAN &amp; ENVIRONMENT</b>	
Average Life	50,000
Operating Temperature	-20°C ~ 45°C



### DIMENSIONS



### ORDERING

ITEM#	DESCRIPTION	WATT	LED	COLOR	LUMENS	CRI	VOLT	HOURS	CASE
CL/LLR305	LED 45.8" 30WT5/50K/FR/PLUG & GO™ - 90465	30	SMD	5000K	3500	82	120-277V	50,000	25

Please check DLC website for the most current list of approved items - [www.designlights.org](http://www.designlights.org)  
Published lumens on LED products are approximate and may vary slightly.