



LMDX22 COMMERCIAL DUTY • 5YR LED SPEC-SELECT™ SNAP & GO™ MAGNETIC MODULES

LINEAR RETROFIT KITS FOR 2X2 LUMINAIRES

FEATURES

- · Adjustable Wattage (3 settings)
- · Adjustable Color (3 settings)
- Quick connect
- · Magnetic mounting
- Innovative design

APPLICATION

Ideal for retrofitting for traditional fluorescent fixtures and recessed troffers in drop-in ceilings.

-	TD	ır	ΛI

Wattage	15W / 20W /25W
Voltage	120-277V
Current	250mA
Power Factor	0.9
Total Harmonic Distortion (THD)	14.2

LIGHTING PERFORMANCE

umens 2250 / 3000 / 3750		
Lumens Per Watt (LPW)	150	
Color Temperature (CCT)	3500K / 4000K / 5000K	
Color Rendering (CRI)	83	
R9 (Red Value)	3	
Beam Angle	118°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B2 - U1 - G1	
Dimmable Lighting Control	('D immable 0-10V, Range 10% - 100%	

ENVIRONMENT

Operating Temperature	-40° ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP20
Fixture Type	Enclosed

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	2835
Driver	937806

CONSTRUCTION

Housing	Plastic
Base / Power Supply	Hard Wired

QUALIFICATIONS

Model Number	93780




Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

LMDX22 COMMERCIAL DUTY • 5YR LED SPEC-SELECT™ SNAP & GO™ MAGNETIC MODULES



DIMENSIONS (Inches)	MODULES	DRIVER
Length	21.8"	14"
Width	0.7"	1.2"
Height		0.8"
Net Weight (Lbs)	1.1	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	10	10811768029526		14
Individual Item	1	811768029529	N/A	N/A
Country of Origin	China			
HS Tariff	9405.11.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
LMDX22	LED SPEC-SELECT™ SNAP & GO™ MAGNETIC MODULES/15-20-25W/35-40-50K/DIMM/120-277V • 2X2FT	10
Manufactured by P.	Q.L., Inc Manufacturer Model # 93780	
ACCESSORIES		
LMDX02	SINGLE FROSTED LENS FOR SPEC-SELECT™ SNAP & GO™ • 2FT	100