



SELECTABLE
COLOR
TEMPERATURE

LPR207 COMMERCIAL DUTY • 3YR
LED TONE-SELECT™ PAR20 LAMP
REFLECTOR (NARROW FLOOD)

FEATURES

- Adjustable color temperature for custom lighting application.
- Superior lighting performance
- Energy efficient
- Innovative and durable design that resembles traditional lighting
- UL 94 V-0: Shatter-resistant, flame-resistant polycarbonate lens
- Ideal replacement for 50W traditional lamps

APPLICATION

Indoor residential and commercial spaces, track lighting and recessed downlights.

ELECTRICAL

Wattage	7W
Voltage	120V
Current	63mA
Power Factor	0.7

LIGHTING PERFORMANCE

Lumens	450
Lumens Per Watt (LPW)	64
Color Temperature (CCT)	27K / 30K / 35K / 40K / 50K
Color Rendering (CRI)	90
Beam Angle	40°
Dimmable Lighting Control	<i>Dimmable</i> see compatibility report

ENVIRONMENT

Operating Temperature	-4° ~ 104°F
Suitable Location	DAMP
Ingress Protection Rating	IP20
Suitable Fixture Type	Open

LIFESPAN

Average Life (Hours)	25,000
Warranty (Years)	3

COMPONENTS

LED Light Source	Lumileds
------------------	----------

CONSTRUCTION

Housing	PC
Base / Power Supply	E26 - Medium
Finish	White

QUALIFICATIONS

Model Number	91949
--------------	-------



Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


LPR207 COMMERCIAL DUTY • 3YR LED TONE-SELECT™ PAR20 LAMP



ITEM INFORMATION

DIMENSIONS (Inches)

Length (MOL)	3.1"
Width/Diameter (MOD)	2.5"
Weight (Lbs)	0.09



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	96	10811768026082	20.6" x 15.5" x 13.5"	11.1
Individual Box	1	811768026085	2.5" x 2.5" x 3.3"	0.11
Country of Origin	China			
HS Tariff	8539.50.0010			

ORDERING

ITEM#	DESCRIPTION	TITLE 20	TITLE 24	CASE
LPR207	LED TONE-SELECT™ 7WPAR20/27-30-35-40-50K/40°/DIMM	Yes	No	96

Manufactured by P.Q.L., Inc. - Manufacturer Model # 91949

ADDITIONAL INFORMATION:

- Using the CCT slider on the side of lamp to select the desired color temperature.