



## LRT147 COMMERCIAL DUTY • 5YR LED 7' LO-PROFILE SURFACE MOUNT LUMINARIES FOR COMMERCIAL AND RESIDENTIAL BUILDINGS

### FEATURES

- LED surface mount fixture provides glare free illumination and even light distribution with a clean, modern look.
- TONE-SELECT™; Select your preferred color temperature
- Diffusing lens
- Low profile design
- Easy installation for J-Box.

### APPLICATION

Perfect for a wide range of applications including offices, hospitals, retail spaces, schools, lobbies, commercial buildings, and work areas.

### ELECTRICAL

Wattage	14W
Voltage	120V
Power Factor	0.9
Total Harmonic Distortion (THD)	20%

### LIGHTING PERFORMANCE

Lumens	830
Lumens Per Watt (Lm/W)	60
Color Temperature (CCT)	2700K / 3000K / 3500K / 4000K / 5000K
Color Rendering (CRI)	90
Beam Angle	120°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	--
Dimmable Lighting Control	See compatibility chart

### ENVIRONMENT

Operating Temperature	-40° ~ 104°F
Suitable Location	DAMP
Ingress Protection Rating	IP20

### LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

### COMPONENTS

LED Light Source	Smalite
Driver	Internal

### CONSTRUCTION

Lens	PC
Base / Power Supply	Hard Wired
Finish	White

### QUALIFICATIONS

Model Number	CDRI-07-14-5C-W
--------------	-----------------



Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

LRT147 COMMERCIAL DUTY • 5YR  
LED 7' LO-PROFILE SURFACE MOUNT





DIMENSIONS (Inches)

Width/Diameter (MOD)	7"
Height	0.6"
Net Weight (Lbs)	--

PACKAGING

Individual Box	1
Dimensions	8.7" x 7.4" x 1.9"
Country of Origin	--
UPC	811768029666



ORDERING

ITEM#	DESCRIPTION	CASE
LRT147	7" ROUND LO-PROF - 14W/ 50-27K/ 12V 5YR	1

Manufactured by P.Q.L., Inc. - Manufacturer Model # CDRI-07-14-5C-W

ITEM INFORMATION