



**SELECTABLE WATTAGE & CCT**

**LVX445** LT. COMMERCIAL • 5YR  
**LED 4' SPEC-SELECT™ VAPOR TIGHT**  
DIRECT LINEAR AMBIENT LUMINARIES

**FEATURES**

Our Spec-Select™ Vapor Tights feature adjustable wattage and color temperature for the perfect balance of light in any application.

- Use 30% less energy than a linear fluorescent fixtures.
- 100% UV stabilized polycarbonate housing and diffusers eliminates glare and produces even light distribution.
- Liquid silicone perimeter gasket
- Stainless steel clips.

**APPLICATION**

Ideal for parking garages, cold storage, food processing facilities, dusty and wet environments.

**ELECTRICAL**

Wattage	34W / 38W / 45W
Voltage	120-277V
Current	0.38-0.16A
Power Factor	0.9
Total Harmonic Distortion (THD)	10

**LIGHTING PERFORMANCE**

Lumens	4420-5850
Lumens Per Watt (Lm/W)	130
Color Temperature (CCT)	3500K / 4100K / 5000K
Color Rendering (CRI)	82
R9 (Red Value)	12 / 18 / 16
R13 (Skin Tones)	84 / 85 / 85
Beam Angle	120°
Light Distribution	Very Short, Type II
BUG Rating (Backlight, Uplight, and Glare)	B2 - U3 - G2
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

**ENVIRONMENT**

Operating Temperature	-40° ~ 113°F
Suitable Location	<b>WET</b>
Ingress Protection Rating	IP66

**LIFESPAN**

Average Life (Hours)	50,000
Warranty (Years)	<b>5</b>

**COMPONENTS**

LED Light Source	Seoul 3528
Driver	SIP50-I1000

**CONSTRUCTION**

Housing	Polycarbonate
Lens	Frosted
Base / Power Supply	Hard Wired
Finish	White

**QUALIFICATIONS**

Manufacturer Model #	55606
----------------------	-------



*Manufactured by P.Q.L., Inc. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.*


# L VX445 LT. COMMERCIAL • 5YR LED 4' SPEC-SELECT™ VAPOR TIGHT



ITEM INFORMATION

### DIMENSIONS (Inches)

Length	47.2"
Width	3.5"
Height	3.1"
Net Weight (Lbs)	4.4



### PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	4	10854432004689	49.5" x 8.5" 71"	24.1
Individual Box	1	854432004682	--	6
Country of Origin	China			
HS Tariff	9405.10.6020			

### ORDERING

ITEM#	DESCRIPTION	CASE
L VX445	LED 4' SPEC-SELECT™ VAPOR TIGHT - 34/38/45W/35-50K/FR LENS/120-277V/DIMMABLE	4

*Manufactured by P.Q.L., Inc. - Manufacturer Model # 55606*

### ACCESSORIES

LF3502	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN/SPLIT TYPE/L T20C (For use with drivers that are 100W or less.)	10
--------	---	----

### ADDITIONAL INFORMATION:

- Default settings; 45W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver. The color temperature and wattage should be selected prior to installation.

