





REPLACES F32T8 FLUORESCENT



- BLACK ENDS
- DIM
- YELLOW
- SHORT LIFE







Zeatures

LONG LIFE DESIGN

- XTREME DUTY LEDs
- 12 year rated components

BRIGHTER WHITER LIGHT

- Under 20% light loss
- 49% Brighter Xtrabrite[™] phosphors

SAVES # 47% ENERGY

- Cool operation
- Low AC costs

SAFE

• No UV / No fading / No Mercury

of BRIGHTER WHITER LIGHT

Improved productivity



Reduced glare & eyestrain



Colors more vibrant



1-3 YEARS

SHORT LIFE LAMPS

CAN BURNOUT AS EARLY AS 1 YEAR





12 YEARS





Division of P.Q.L., Inc.

LED Lamp Specifications

Product Code = PLT517

Description = L17T8/AWX8350/D.I./LED

Type = LED (Fluorescent Retrofit)

Color Temperature = 5000° Kelvin

Color Rendering Index (CRI) = 83

Ballast Type = Electronic F32T8 Instant Start (IS) or Program Start (PS)

(Not for use on magnetic or T12 ballasts)

Operating Temperature = -10° F to 110° F

Projected Photopic Lumens = 2445 (at N.B.F.)

Projected Seeable LumensTM = 4523 (at N.B.F.)

Nominal Length = 48"

Diameter = 1"(T8)

Nominal Wattage = 17w (at N.B.F.)

Base = Medium Bi-Pin (G13)

End Pins = Brass

End Cap = Aluminum – Gold Color

LED Chips = 34

Mercury/UV = None/None

UL Listed = Yes

DLC Listed = Yes

Dimmable = Yes

Warranty = 12-years with LBF and NBF ballasts

(5-years with HBF ballasts)

*Specifications subject to change without notice.

101817





Division of P.Q.L., Inc.

LED Lamp Specifications

Product Code = PLT617

Description = L17T8/VLX8355/D.I./LED

Type = LED (Fluorescent Retrofit)

Color Temperature = 5500° Kelvin

Color Rendering Index (CRI) = 83

Ballast Type = Electronic F32T8 Instant Start (IS) or Program Start (PS)

(Not for use on magnetic or T12 ballasts)

Operating Temperature = -10° F to 110° F

Projected Photopic Lumens = 2445 (at N.B.F.)

Projected Seeable LumensTM = 4529 (at N.B.F.)

Nominal Length = 48"

Diameter = 1"(T8)

Nominal Wattage = 17w (at N.B.F.)

Base = Medium Bi-Pin (G13)

End Pins = Brass

End Cap = Aluminum – Gold Color

LED Chips = 34

Mercury/UV = None/None

UL Listed = Yes

DLC Listed = Yes

Dimmable = Yes

Warranty = 10-years with LBF and NBF ballasts

(5-years with HBF ballasts)

061417



^{*}Specifications subject to change without notice.