



## LFC275 LT. COMMERCIAL • 5YR **LED CANOPY**

**PARKING GARAGE LUMINAIRES** 

#### **FEATURES**

- · Ultra-thin design.
- Replaces 100-175W MH

#### **HOUSING**

- · One piece sealed die cast housing.
- · UV stabilized polycarbonate optical lens.

#### **MOUNTING**

- Surface Mount with J-Box.
- · Pendant with 3/4" conduit.

#### **APPLICATION**

Parking structures and storage areas.

#### **ELECTRICAL**

Wattage	21W
Voltage	120-277V
Current	
Power Factor	0.9
Total Harmonic Distortion (THD)	
LIGHTING PERFORMANCE	
Lumens	3045
Lumens Per Watt (Lm/W)	145
Color Temperature (CCT)	5000K
Color Rendering (CRI)	80
R9 (Red Value)	
R13 (Skin Tones)	
Beam Angle	100° x 60°
Light Distribution	Type VS
Dimmable Lighting Control	<b>Dimmable</b> 0-10V, Range 10% - 100%

Operating Temperature	-40° ~ 104°F
Suitable Location	WET
Ingress Protection Rating	IP65

#### LIFESPAN

Warranty (Years)	5
Warranty (Years)	5

#### **COMPONENTS**

LED Light Source	Seoul 3528
Driver	

#### **CONSTRUCTION**

Housing	Aluminum		
Lens	PC / Frosted		
Base / Power Supply	Hard Wired		
Finish	Black		

### **QUALIFICATIONS**

Manufacturer Model # 83086




Manufactured by P.Q.L., Inc. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

# LFC275 LT. COMMERCIAL • 5YR LED CANOPY



#### **DIMENSIONS** (Inches)

Length	10.4"
Width/Diameter	10.4"
Height	3.5"
Weight (Lbs)	



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	<b>GROSS WEIGHT</b> (Lbs)
Master Carton	4	10811768027706	19.3" x 19.3" x 12.2"	7.3
Individual Box	1	811768027709		1.8
Country of Origin	China			
HS Tariff	9405.99.4090			

#### **ORDERING**

ITEM#	DESCRIPTION	CASE
LFC275	LED CANOPY 21W/50K/120-277V/BLACK/DIMMABLE/V4	4

Manufactured by P.Q.L., Inc. - Manufacturer Model # 83086

#### **ADDITIONAL INFORMATION:**

**Note:** To prevent water damage which may shorten the life of an exterior mounted fixture; the fixture should be properly weather sealed according to the installation instructions or between the fixture base and mounting surface. Damage due to improper installation may void the warranty.